





SECURITY ACCESS PANELS

Trafalgar Security Access Panels are manufactured in Australia and have been designed for use where there is a need to provide security as well as access.

Trafalgar Security Access Panels allow for an aesthetically pleasing means of providing secure access into walls and ceilings, and are fully customisable to meet any security specification.



KEY FEATURES

- Australian made quality
- Anti-ligature and anti-tampering design
- Fully welded, pre-primed and ready for installation
- Wide range of lock and panel specifications
- Fully customisable



APPLICATIONS

- Health care
- Mental health wards
- Correctional centres
- Police stations
- Banks
- Defence
- Airports



TRADES











TABLE OF CONTENTS



Secti	ion	Page
Secui	Security Access Standard Range	
Custo	Custom Access Panels	
Speci	fications	5
Fram	e Type: Flanged Edge (SAP-FE)	6
Fram	e Type: Wet Wall(SAP-WW)	7
ation	Plasterboard	8
Installation	Masonry	9
Drawing	Security Access Panel - Plasterboard/Masonry	10
Technical Drawing	Security Access Panel - Plasterboard/Masonry- Install Profile	11
FAQ		12
Custo	om Order Forms	13-15

SECURITY ACCESS STANDARD RANGE



SPECIFICATIONS

THE TRAFALGAR ACCESS DIFFERENCE			Others	
DOOR PANEL	Steel construction with optional MDF or steel rib inserts for durability and/or weight reduction, pre-primed for ease of installation and finishing.	✓	?	
FRAME	Fully welded steel frame, pre-primed for ease of installation and finishing	✓	?	
NOMINALLY SIZED	Trafalgar Steel Access Panels are manufactured 5mm smaller than the nominal size for ease of installation in uneven openings (i.e. a 600 x 600mm Security Access Panel is designed for installation into a 600 x 600mm opening)	✓	?	
HARDWARE OPTIONS	Made in Australia to suit Australian security specifications. A range of hardware (including SCEC-endorsed locks) is available to meet your security specifications	✓	?	
HINGE	Welded-pin continuous piano hinge that is flush with the door panel to prevent damage/unintended access	✓	?	
RANGE OF STANDARD OPTIONS	Available with a broad range of standard options • Lock shrouds to prevent unintended access • Perforated doors for airflow requirements • SCEC-endorsed lock options • Gas struts for access safety	√	?	
PACKAGING	Packaged to avoid freight damage	√	?	
CUSTOMISATION AVAILABLE	Made in our South Granville, NSW factory and supported by our team of engineers, the Trafalgar SAP can be customised quickly and cost effectively to suit your projects needs	✓	?	

Trafalgar Access also supplies a comprehensive range of fire rated, acoustic, customwood, tileable and specialty Access Panels.





MADE LOCALLY MEANS VERSATILITY





OVERSIZED

Customisation options include:



- A huge range of sizes including odd shapes and oversized
- **?** Single and double doors
- **?** Flanges, latches, and hinges
- **?** Panel material including stainless steel
- ? Colour options

All this made locally means fast turn around.

Talk to the Trafalgar Team today to design your custom Access Panel.*

*Customisation options limited for Acoustic and Fire Rated Access Panel ranges.





SPECIFICATIONS




	Low	Medium	High	
FRAME SPECS	1.1mm ZA steel	1.6mm ZA steel	1.6mm ZA steel	
FRAME PROFILE	55mm	100mm	105mm	
DOOR PROFILE	24mm	28mm	37mm	
DOOR SPECS	-1.1mm ZA steel door	-1.6mm ZA steel door	-2.0mm ZA steel door	
	-No infill	-No infill	-MDF infill	
	-1.1mm ZA backpan	-1.6mm ZA backpan	-1.6mm backpan	
DOOR OPTIONS	-MDF infill -Steel rib infill -Perforated door	-MDF infill -Steel rib infill -Perforated door -Gas Strut (For Large Panels)	-Steel rib infill -Perforated door -Gas Strut (For Large Panels)	
LOCK (STANDARD)	Key Cam	Kaba Nightlatch (with lock box)	SCECL3 Bilock	
LOCK OPTIONS	-Kaba Nightlatch (with lock box) - Lockwood 201	SCECL2 lock -SCECL3 lock - Lockwood 201	-Kaba Nightlatch (with lock box) -SCEC Mortice Lock - Lockwood 201	
HINGE	Piano hinge	Piano hinge (heavy duty)	Piano hinge (heavy duty)	
WEIGHT (450 X 450 STANDARD) WILL VARY ACCORDING TO OPTIONS SELECTED	5kg	11kg	16kg	
CUT-OUT SIZE	Cut out size should be the same size as the access panel.			
CO1-OO1 312E	For example, 450 x 450 access panel will have a 450 x 450 cutout			
FRAME TYPES		Flanged Edge (FE) (Feathered Edge or Picture Frame) Wet Wall (WW) (Set Bead or Concealed Frame) Stainless Steel (Optional)		
	Trafalgar can custom manufacture to meet your specifications. Trafalgar also supply a comprehensive			
ALSO AVAILABLE	range of fire rated, metal, customwood, tileable and specialty Access panels.			



Frame Type FLANGED EDGE (FEATHERED EDGE)

Picture frame







Panel installed (SAP-M-450-FE shown)

STANDARD RANGE

Model	Panel FE Steel panel door + picture frame pre-primed	Lock	Item Number	Dimensions (mm)	Frame Depth	
	Key Cam (standard, options available)	Key Cam (standard, options available)	SAP-L-300-FE	300 x 300 mm	55mm	
Low Security Access Panel			SAP-L-450-FE	450 x 450 mm		
			SAP-L-600-FE	600 x 600 mm		
	Kaba Nightlatch (standard, options available)	SAP-M-300-FE	300 x 300 mm			
Medium Security Access Panel			SAP-M-450-FE	450 x 450mm	100mm	
			SAP-M-600-FE	600 x 600 mm		
	SCECL3 Bilock (standard, options available)		SAP-H-300-FE	300 x 300 mm		
High Security Access Panel			SAP-H-450-FE	450 x 450mm	105mm	
		SAP-H-600-FE	600 x 600 mm			



Frame Type WET WALL (PERFORATED EDGE)







Depth

55mm

(SAP-M-450-WW Shown)

STANDARD RANGE					
del	Panel WW Steel panel door + picture frame pre-primed	Lock	Item Number	Dimensions (mm)	Frame [



Low
Security
Access
Panel

Mod









SAP-M-300-WW

SAP-M-600-WW

SAP-L-450-WW

SAP-L-300-WW





300 x 300 mm

600 x 600 mm

300 x 300 mm

450 x 450 mm



High Security Access

Panel



Kaba Nightlatch (standard, options available)





450 x 450mm

600 x 600 mm



105mm





SCECL3 Bilock (standard, options available)



SAP-H-300-WW

SAP-H-450-WW

SAP-H-600-WW

450 x 450mm

300 x 300 mm

600 x 600 mm





INSTALLATION

PLASTERBOARD






Mark and cut out hole the same size as the access panel nominal size. For a 600×600 mm nominal Security Access Panel, the ideal cut-out size is 600×600 mm.

PREPARE




The opening must be framed with studs / noggings to affix the panel to.

FIT



With the door open, screw the frame into the wall/ceiling through the pre-formed fixing holes (200mm centres recommended).

FIX



Fixings must be appropriate for the wall/ceiling – Anti-tamper 10g screws are recommended in the absence of a specified fixing.

INSTALLATION

MASONRY

MARK



Mark and cut out hole the same size as the access panel nominal size. For a 600x600mm nominal Security Access Panel, the ideal cut-out size is 600x600mm.



With the door open, screw the frame into the wall/ceiling through the pre-formed fixing holes (400mm centres recommended).




Fixings must be appropriate for the wall/ceiling – Anti-tamper 6mm masonry anchors are recommended in the absence of a specified fixing.




TECHNICAL DRAWING


SECURITY

Note: All measurements are in millimeters (mm)












TECHNICAL DRAWING

SECURITY

Note: All measurements are in millimeters (mm)









FAQ

Q Can we install this panel into a floor?

A No, these Security Access Panels are for wall and ceiling applications only.

Q Does this panel have an acoustic rating?

A Yes, If you require acoustic security panels please contact the Trafalgar access team on 1800 888 714 to discuss your requirements.

Q Is this access panel for low, medium or high risk areas?

A We manufacture access panel across varying security levels to meet your needs, please contact the Trafalgar access team on 1800 888 714 to discuss your requirements..

Q What if I don't need such a high security panel for my application?

A Call the Trafalgar Access team on 1800 888 714 and we can discuss our low and medium security options to provide a solution.

Q What prevents someone in the ceiling space opening the panel and gaining access?

A Our medium security SAP comes standard with a securely fitted lock box on the back of the panel to prevent unwanted access. Alternate lock options and/or lock boxes can be fit to the SAP range to prevent access from the unsecured side.

Q I have an unusual application, can you manufacture a safe upward opening security panel?

A Yes, call the Trafalgar Access team on 1800 888 714 to discuss your requirements.

Q Is this panel anti-ligature?

A Yes, Trafalgar Access has designed an anti-ligature and anti-tampering high Security Access Panel. Please note that while the Access Panel is designed with this in mind, the installation and any additions to the panel (handles,etc) may reduce the effectiveness of these features.

Q Can I have this access panel powder coated?

A Yes, Please contact the Trafalgar Access team on 1800 888 714 to discuss your requirements.

9

SOCIAL MEDIA












LOW SECURITY ACCESS PANEL ORDER CONFIRMATION

Customer to complete for each size panel required. All panels will be manufactured 5mm smaller than the opening size in wall or ceiling to a tolerance of +/-2mm. It is designed for easy install.








MEDIUM SECURITY ACCESS PANEL ORDER CONFIRMATION

Customer to complete for each size panel required. All panels will be manufactured 5mm smaller than the opening size in wall or ceiling to a tolerance of +/-2mm. It is designed for easy install.







HIGH SECURITY ACCESS PANEL ORDER CONFIRMATION

Customer to complete for each size panel required. All panels will be manufactured 5mm smaller than the opening size in wall or ceiling to a tolerance of +/-2mm. It is designed for easy install.

