














AIRTIGHT ACCESS PANEL ORDER CONFIRMATION

Customer to complete for each size panel required. All panels will be manufactured 5mm smaller than the opening size in wall or ceiling to a tolerance of +/-2mm. It is designed for easy install.

Opening size in ceiling or wall:		Height	mm	Width	mm
Step 1 APPLICATION  Wall  Ceiling	Step 2 FRAME TYPE  Flanged Edge (Feathered Edge or Picture Frame)  Wet Wall (Seat Bead or Concealed frame)	Step 3 LOCK OPTIONS <i>Front Door</i>  Invisible Touch latch (standard)  Key Cam  Kaba Nightlatch <i>Rear Door (affects leakage rate, see tech manual)</i>  Silver Square Cam (low leakage)  Screw Fixed (standard airtight)			
SEAL Kilargo IS1046si 	Step 4 FINISH Pre-primed white (standard) Antimicrobial powder coat Other (please specify in 'Special Instructions')				
FRAME PROFILE  Flanged Edge Cross Section  Wet Wall Cross Section	Special Instructions				
CLICK THE IMAGE TO VISIT OUR WEBSITE  www.taccess.com.au		Quantity Company name Contact Name Date Signature			
		<small>*By signing and returning this order confirmation, you are agreeing to the manufacture of a custom panel subject to Trafalgar's Terms and Conditions.</small>			